

The right tyre for every application

CGS TYRES

Agricultural and industrial tyres

PRODUCT HIGHLIGHTS



Drive wheel radial tyre



RD-03

The new 65 Series wide tyre for tractors with up to 200 hp

- radial tyre, approved for speeds of up to 65 km/h (40 mph)
- larger ground contact patch for high yields per hectare
- up to 40% higher tractive force compared with standard tyres
- uniform ground pressure thanks to even tread contour
- reduced fuel consumption

Size range available:

480/65 R 24*	133D	600/65 R 34*	151D
480/65 R 28	136D	600/65 R 38	153D
540/65 R 28	142D	650/65 R 38	157D
600/65 R 28	147D	710/70 R 38	166D
540/65 R 30	150D	650/65 R 42	165D

* in preparation

Drive wheel radial tyre



RD-02

The economical 70 Series tyre with high tractive force

- radial tyre, approved for speeds of up to 50 km/h (31 mph)
- gentle ground handling, thanks to lower inflation and ground pressure
- high transmission of tractive forces through large ground contact patch
- identical load capacity at 50 km/h (31 mph) and 40 km/h (25 mph) (A8 = B)
- increased driving comfort thanks to a supple sidewall

Size range available:

320/70 R 24*	116B	480/70 R 30	141B
380/70 R 24	125B	480/70 R 34	143B
420/70 R 24*	130B	480/70 R 38	145B
380/70 R 28	127B	520/70 R 38	150B
420/70 R 28	133B	580/70 R 38*	155B
480/70 R 28	140B		

* Tread pattern version RD-70

Drive wheel radial tyre



RD-01

The new generation 85 Series standard tyre

- radial tyre, approved for speeds of up to 50 km/h (31 mph)
- high traction with low slip
- gentle ground handling, thanks to low inflation pressure
- optimum driving comfort through circumferentially orientated tread lugs
- reduced fuel consumption, thanks to low rolling resistance

Size range available:

280/85 R 24	112B	380/85 R 28	130B	340/85 R 36	129B
320/85 R 24	119B	420/85 R 28	136B	340/85 R 38*	133B
340/85 R 24	122B	380/85 R 30*	135B	420/85 R 38	141B
380/85 R 24	128B	420/85 R 30	137B	460/85 R 38	146B
420/85 R 24*	137B	460/85 R 30	142B	520/85 R 38	152B
280/85 R 28	115B	320/85 R 32*	142B	520/85 R 42*	162B
320/85 R 28	121B	420/85 R 34	139B		
340/85 R 28	124B	460/85 R 34	144B		

* in preparation

Flotation tyres



AR-01

Radial tyre for trailers used in agriculture and with utility vehicles

- approved for speeds of up to 80 km/h (50 mph)
- all-steel design for high durability
- high mileage performance
- reduced fuel consumption, thanks to low rolling resistance

Size range available:

385/65 R 22.5 (15 R 22.5)	161F
445/65 R 22.5 (18 R 22.5)	169F



AR-02

Radial flotation tyre with attractive tread pattern design

- approved for speeds of up to 65 km/h (40 mph)
- good traction and self-cleaning
- reduced fuel consumption, thanks to low rolling resistance

Size range available:

560/60 R 22.5	161D
---------------	------



MPT-20

Versatile MPT radial tyre, particularly suitable for use on utility vehicles

- approved for speeds of up to 110 km/h (68 mph), directionally orientated
- good traction, also in winter use
- outstanding driving comfort
- even wear

Size range available:

335/80 R 20 (12.5 R 20)	147K
365/80 R 20 (14.5 R 20)	152K



MPT-21

MPT radial tyre for mixed applications both on and off the road

- approved for speeds of up to 100 km/h (62 mph), non-directional tread
- particularly good traction and self-cleaning
- good driving characteristics
- also available as an EM tyre

Size range available:

335/80 R 20 (12.5 R 20)	139J
365/80 R 20 (14.5 R 20)	152J
405/70 R 20 (16/70 R 20)	152J
405/70 R 24 (16/70 R 24)	152J



MPT-22/EM-02

MPT and/or EM radial tyre with tractor tread pattern, suitable for all-round applications

- approved for speeds of 50 or 90 km/h (31 / 56 mph)
- outstanding traction and self-cleaning
- comfortable on the road, thanks to steel belt
- highly economical through low wear tread compound

Size range available MPT-22:

335/80 R 18 (12.5 R 18)	132G
445/70 R 24 (17.5L R 24)	151G

Size range available EM-02:

335/80 R 18	139B (151A2)
440/70 R 24	147B (164A2)



EM-01

Radial tyre with versatile tread pattern suitable for a wide range of light earth-moving tasks

- non-directional off-road tread pattern, approved for speeds of up to 50 km/h (31 mph)
- even ground pressure distribution
- good traction and self-cleaning
- good driving characteristics on the road, with lateral stability
- also available as an MPT tyre

Size range available:

365/70 R 18 (14.5/70 R 18)	135B
405/70 R 18 (16/70 R 18)	141B & 156B
335/80 R 20 (12.5 R 20)	136B
365/80 R 20 (14.5 R 20)	141B
405/70 R 20 (16/70 R 20)	143B
405/70 R 24 (16/70 R 24)	146B



ERL-20/ERD-20

High-traction tyre for use on **soft ground** with wheeled loaders (ERL) and dumper trucks/scrapers (ERD)

L2 / G2 / E2

Sizes and versions in preparation:

17.5 R 25	*L2/G2
20.5 R 25	*L2/**E2
23.5 R 25	*L2/**E2



ERL-30/ERD-30

Rugged tyre for use on **hard ground** with wheeled loaders (ERL) and dumper trucks/scrapers (ERD)

L3 / E3

Sizes and versions in preparation:

17.5 R 25	*L3
20.5 R 25	*L3/**E3
23.5 R 25	*L3/**E3

Check the Technical Manual for our full range!



Distributor / customer service

Technical modifications and errors in print, text or pictures excepted.
© Mitas a.s., Czech Republic